



IR-25M Full-HD Network Bullet

CAM6752FIR-PoE CAM6752FIR-W



- ▶ Mega-Pixel CMOS Sensor
- ▶ Resolution up to 1920x1080@30FPS
- ▶ Auto Focus Motorized 4.2x Zoom Lens
- ▶ Embedded ICR and 25-meters IR LED for day & night 24-hours surveillance
- ▶ Two-way audio, Digital In/Out
- ▶ IP66 water proof standard
- ▶ "Corridor Mode" for monitoring stairs, alley way and tunnel in vertical direction
- ▶ Free 36CH recording software
- ▶ Free App (Wecam_p2p) for monitoring via Android/iOS smart phone

Specification

Hardware

CPU	Multimedia SoC
RAM	256MB
Flash ROM	16MB
Image Sensor	1/2.7" Mega-Pixel CMOS
Lens	Auto Focus 4.2X Zoom Lens, Vari-focal length 2.8~12mm , F1.4, Mega-Pixel lens, Motorized
IR Distance	25 Meters
IR LED	28 + 2 Units High Power IR LEDs
Min. Illumination	Color: 0.05 lux (AGC ON) Mono: 0.01 lux (AGC ON)
Day / Night	Built-in Mechanism IR Cut Filter (ICR)
DC Iris	Yes
Shutter Time	Auto: Indoor, Outdoor Manual: 1/30 ~ 1/1000 sec
Audio Input	1 Microphone in (3.5mm phone jack)
Audio Output	1 Line out (3.5mm phone jack)
Digital In / Out	1 Digital in / 1 Digital out (Terminal block)
Video Output	1 Analog video out (BNC connector)
Housing	IP66 water proof standard
Power Supply	CAM6752FIR-W: Use Power Adaptor: DC 12V, 1.5A CAM6752FIR-PoE (built-in PoE Splitter): Use PoE: PoE Injector (IEEE 802.3af) Or, use Power Adaptor: DC 12V, 1.5A
Consumption	Max. 10.5 Watt
Dimensions	Φ83 x L180mm (w/o stand)
Operating Temp.	-10°C ~ +50°C

Network

Ethernet	10 / 100 Base-T
Wireless	802.11b/g/n, supports WPA-PSK,
CAM6752FIR-W	WPA2-PSK, WEP 64/ 128 bit
Network Protocol	IPv4/IPv6, HTTP, HTTPS, TCP/IP, RTP/RTSP, UDP, 3GPP, SMTP, FTP, Samba, PPPoE, DHCP, DDNS, NTP, UPnP, SNMP, QoS/DSCP, IP Filter, IEEE 802.1x, Bonjour
Onvif Compliance	Onvif V2.20, 1.01

Micro SD Card Management

Recording Trigger	Motion Detection, Digital In, Tampering Detection, IP Check, Network Disconnect
Schedule	Snapshot with schedule
Video Format	Video (AVI), Snapshot (JPEG)
Playback / Delete	Yes

System

Video Resolution	1920x1080, 1280x720, 640x480, 320x240, 176x144
Video Format	H.264 / MJPEG
Frame Rate	Up to 30 FPS
Triple Streaming	2 for PC live view, 1 for mobile live view
Video Direction	Normal: Landscape 16:9 Corridor Mode: Vertical 9:16, 90° / 270°
Bitrate Adjust	CBR / VBR, up to 8Mbps
Video Adjustment	Brightness, Contrast, Hue, Saturation, Sharpness, Gain control, Shutter time, Sense Up, Digital WDR, Anti Fog, Lens Distortion Correction, White Balance, 3D/2D Digital Noise Reduction, Day/Night color mode, Video orientation
Audio Format	G.711 (64Kbps)G.726 (24Kbps / 32Kbps)
Privacy Mask	3 definable areas
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, IEEE 802.1x port-based authentication, QoS/DSCP
Firmware Upgrade	HTTP mode, can be upgraded remotely

Event System

Event Trigger	Motion Detection, Digital In, Tampering Detection
Trigger Actions	Send Email, Send to FTP, Save to SD Card, Save to Samba HDD, Digital Out
Motion Area	3 definable areas
Pre / Post Alarm	Yes, configurable time

Remote Client Access

Client Software	Microsoft IE V7.0 (32-bit) or above Safari V5.1 or above Google Chrome V13.0 or above Android / iOS smart phone: "wecam_p2p"
Connected Clients	Up to 10 clients simultaneously
PC Requirement	OS: Windows 7, Vista, XP Suggested Hardware: Intel Core 2 Duo 2.53GHz, RAM: 1GB Graphic card: 128MB onboard