



# 1080P CMOS Day&Night IP Camera

# CAM743FICR (W,PoE)



- ▶ H.264 / MJPEG Dual mode & 6 stream
- ▶ 30FPS @ 1920x1080
- ▶ Support Micro-SD card for event recording
- Onvif Compliant
- Support DC IRIS
- ▶ 2-way audio / 1 Analog video output
- ▶ Digital I/O: 1 in / 1 out
- → 3GPP for monitoring via smart phone
- Optional Wireless (CAM743FICR-W)
- Embedded PoE (CAM743FICR-PoE)

# Specification

### **Hardware**

Image Sensor 1/2.7" CMOS, 2 Mega-Pixels

Lens Fixed Lens, Focal Length 3.6 mm, F1.8

Illumination 1 lux

Day/ Night Mechanism IR Cut Filter (ICR)

Lens Changeable Yes, CS Mount

Support DC IRIS Yes

Video Out 1 Analog video out (BNC connector)

Audio In 1 Mic in Audio Out 1 Line out

Digital I/O Digital 1 In / 1 out

Power Supply CAM743FICR: DC 12V, 1A

CAM743FICR-PoE:

Use PoE: PoE Injector (IEEE 802.3af) Or, use Power Adapter: DC 12V, 1A

Dimensions W65 x H52 x L84 mm

Temperature  $-10^{\circ}\text{C} \sim +45^{\circ}\text{C}$ 

## **Network**

Ethernet 10/ 100 Base-T

Wireless 802.11 b/g/n (CAM743FICR-W)

Network Protocol HTTP, HTTPS, TCP/IP, UDP, SMTP, FTP,

PPPoE, DHCP, DDNS, NTP, DNS, ARP, RTSP,

RTP, UPnP

# **SD Card Management**

Recording Trigger Motion Detection, Schedule, By boot,

GPPIN

Video Format Video (AVI), Snapshot (JPEG)
Schedule Snapshot during schedule

Video Playback Yes

#### **System**

Video Resolution 1920x1080, 1280x720, 640x360,

320x180, 160x128

Compression Format H.264 / MJPEG

Frame Rate Up to 30 FPS@1920x1080

Video Bitrate Adjust CBR, VBR

Dual Streaming Yes

3GPP Yes, Live view with smart phone
Video Adjust Brightness, Contrast, Hue, Sharpness

Saturation, Contrast, Auto Gain Control, Exposure control, White

balance, Flip / Mirror, Rotation, WDR,

De-noise

Motion Detection Yes, 3 different areas
Pre/ Post Alarm Yes, configurable
Security Password protection

Connection Up to 10 clients simultaneously

Firmware Upgrade HTTP mode, remotely

Audio Yes, 2-way

#### **Event System**

Event Trigger Schedule, Motion Detection, By boot,

GPPIN

Trigger Actions Send Email, Send to FTP, Save to SD

Card, Digital Out

## **Client Requirements**

OS Windows XP / Vista / Win 7

Browser IE7,IE8, FireFox,Safari,Chrome, Opera Suggested Intel Core 2 Duo 1.66GHz, RAM: 1GB Graphic card: 128MB onboard RAM

#### **Package List**



S do

doesn't include power adaptor

PoE Model

CD & Manual Stand

nd [

thernet Adaptor cable