



16CH Network Video Recorder.

NVR6016LX-RAID

16CH

9HDD

RAID

5MP
Camera

1080P
Video

eSATA

8-Alarm
Input

PTZ
Virtual
Panel

Free
Android
APP

Free
iOS
APP

Product Overview

Asoni NVR6016LX-RAID is a professional network video recorder with high capacity storage. The built-in RAID system manages up to 9 HDDs and 36TB total storage, and you can expand the recording space with an eSATA external storage if necessary. With 100Mbps throughput, the NVR can record and view up to 16pcs of 5 Mega-pixel IP cameras simultaneously.

Asoni NVR6016LX-RAID can be quickly and easily configured into your existing local network along with Asoni H.264 IP cameras. You can control, record, and view live videos right on local display monitor, or through a web browser from PC on the network.

When you are on the road or travel away from your home or office, Asoni NVR6016LX-RAID gives you the same level of user experience as you are inside your home or office network.

Features

- ▶ Linux-based standalone NVR
- ▶ Manage up to 16 IP cameras
- ▶ Supports 5 Mega-pixel IP cameras
- ▶ Up to 480FPS, each channel@30FPS
- ▶ Manual / schedule / event recording
- ▶ Various types of event alerts
- ▶ Built-in 2 RAID controllers, supports RAID-1 / RAID-5
- ▶ Supports SATA HDD x 9 (Max. 36TB)
- ▶ eSATA connector connects to external storage for expansion
- ▶ Supports HDMI/ VGA connectors, display resolution up to 1920x1080
- ▶ 100Mbps throughput
- ▶ Remote client access and management
- ▶ Free App (iCAM Smart) for monitoring via Android / iOS smart phone
- ▶ Supports multiple languages

System

| | |
|-------------------|--|
| CPU / OS | ARM Cortex 9 / Embedded Linux |
| Network | Dual Gigabit Ethernet ports |
| Video Output | VGA x 1, HDMI x 1, up to 1920x1080 |
| USB Connector | USB 2.0 x 2, for mouse or USB storage |
| eSATA Connector | eSATA x 1, for external eSATA storage |
| Audio Input | 3.5mm jack to connect microphone |
| Audio Output | 3.5mm jack to connect amplified speaker |
| Digital I/O | Digital Input x 8, Relay Output x 1 |
| Record Storage | Internal Storage: RAID Controller 1: SATA HDD x 4 RAID Controller 2: SATA HDD x 5 Mode: None-RAID, up to 36TB total RAID-1, up to 16TB total RAID-5, up to 28TB total External Storage: eSATA HDD |
| Network Protocol | HTTP, TCP/IP, RTP/RTSP, 3GPP, SMTP, FTP, PPPoE, DHCP (Server & Client), DDNS, NTP, UPnP |
| Mouse Control | Yes |
| Authority Control | Password protection |
| System Monitor | Watchdog |
| Power Supply | DC 12V, 5A |
| Dimensions | W430 x H88 x D382 mm |
| Operating Temp. | 0~45°C / 32~113°F |
| Humidity | 0~80% RH (non-condensing) |

Video / Audio

| | |
|---------------|--|
| Channel | Max. 16 channels recording and display |
| Support IPCam | Up to 5 Mega-pixel 2592x1944 H.264, MJPEG compression mode |
| Frame Rate | Up to 30FPS per channel |
| Throughput | Up to 100Mbps |
| 2-Way Audio | Hearing voice from IP camera Chatting or broadcasting to IP cameras |

Recording

| | |
|-------------------|---|
| Record Format | Depends on IP camera |
| Record Resolution | Depends on IP camera Up to 5 Mega-pixel 2592x1944 |
| Record FPS | Depends on IP camera, up to 30FPS |
| Record Mode | Manual / Schedule / Event |
| HDD Management | Overwrite when HDD is full Auto delete after selected days |

Live View

| | |
|--------------------|--|
| Split Screen | 1, 4, 9, 16, Full screen |
| Event Notification | On screen icon / buzzer notification |
| PTZ Control | Yes |
| Digital Zoom | Yes |
| Privacy Mask | Yes |
| Channel Identify | Yes, Max. 20 characters for channel name |

Playback and Backup

| | |
|---------------|---|
| Search Method | Date / Time / Event, select from calendar |
| Log Search | Select video from Log table |
| Backup | Backup to USB storage |

Event System

| | |
|-----------------|---|
| Event Trigger | Motion / Digital Input / Video Loss |
| Trigger Actions | Recording / E-Mail / FTP / Buzzer Warning |

Remote Client Access

| | |
|-------------------|---|
| Client Software | Windows PC: IE V7.0 (32-bit) or above Android / iOS smart phone: "iCAM Smart" |
| Connected Clients | Up to 4 clients simultaneously |
| Remote Operation | Live view / Playback / Setup / Backup |
| PC Requirement | OS: Windows 7, Vista, XP Suggested Hardware: Intel Core 2 Duo 2.53GHz, RAM: 1GB |

Packing Content



Connection Diagram

