



H.264 Network Video Server

SVR710-PoE



- ▶ H.264 / MJPEG Dual mode & 6 stream
- ▶ Support Micro SD card for event recording
- ▶ 2-way audio
- ▶ Compact size for installation easily
- ▶ 3GPP for monitoring via 3G mobile phone
- ▶ Support RS-485 for PTZ
- ▶ Embedded PoE (SVR710-PoE)

Specification

Hardware

Video In	1 In (BNC connectors)
Audio In / Out	1 Line in / 1 Line out
RS-485	1, for PTZ control
Power Supply	SVR710: DC 12V, 1A SVR710-PoE: Use PoE: PoE Injector (IEEE 802.3af) Or, use Power Adapter: DC 12V, 1A
Dimensions	W57 x H28 x D110 mm
Temperature	-10°C ~ +45°C

Network

Ethernet	10/ 100 Base-T
Network Protocol	HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP

Event System

Event Trigger	Schedule, Motion Detection, By boot
Trigger Actions	Send Email, Send to FTP, Save to Micro SD Card

Client Requirements

OS	Windows XP / Vista / Windows7
Browser	IE7, IE8, FireFox, Safari, Chrome, Opera
Suggested	Intel Core 2 Duo 1.66GHz, RAM: 1GB Graphic card: 128MB onboard RAM

Micro SD Card Management

Recording Trigger	Schedule, Motion detection, By boot
Video Format	Video (AVI)
Schedule	Snapshot during schedule
Video playback	Yes

System

Video Resolution	NTSC: 720x480, 352x240, 176x120 PAL: 720x576, 352x288, 176x144
Compression Format	H.264 / MJPEG
Frame Rate	Up to 30 FPS
Video Bitrate Adjust	CBR, VBR
Dual Streaming	Streaming1: H.264 / MJPEG Streaming2: H.264 / MJPEG
3GPP	Yes, Live view with 3G mobile phone
Image Snapshot	Yes
Video Adjust	Brightness, Contrast, Saturation, Hue, Rotation
Privacy Mask	Yes, 3 different areas
Motion Detection	Yes, 3 different areas
Pre / Post Alarm	Yes, configurable
Remote PTZ Control	Yes, via RS-485
Security	Password protection
Connection	Up to 10 clients simultaneously
Firmware Upgrade	HTTP mode, remotely
Audio	Yes, 2-way

Package List



CD & Manual Ethernet cable